



## How to Order - Bleed Valves

Compact, convenient, and 100% factory tested, SSP's bleed valves are used to vent signal line pressure to atmosphere before the removal of an instrument or calibration of a control device. SSP Bleed Valves are for systems up to 10,000 PSIG and are available in 316 Stainless Steel and Brass in sizes ranging from 1/8" through 1/2".

### Part Number Configuration



#### Material Designator:

Stainless Steel - 316 / Carbon Steel - CS / Monel - M / Brass -B

#### Options:

Barbed Vent Tube - C3 / 316 SS Bar Handle - TBH

END CONNECTION		BASIC ORDERING NUMBER	DIMENSIONS							
TYPE	INLET SIZE		A IN.	A MM.	B IN.	B MM.	C IN.	C MM.	D IN.	D MM.
MALE NPT	1/8 in.	BV2PM	1.34	34.0	0.94	23.9	0.41	10.4	0.75	19.1
MALE NPT	1/4 in.	BV4PM	1.34	34.0	0.94	23.9	0.41	10.4	0.75	19.1
MALE NPT	3/8 in.	BV6PM	1.47	37.3	1.03	26.2	0.44	11.2	0.88	22.4
MALE NPT	1/2 in.	BV8PM	1.47	37.3	1.03	26.2	0.44	11.2	0.88	22.4
MALE SAE	1/4 in., 7 16-20	BV4PMST	1.34	34.0	0.94	23.9	0.41	10.4	0.69	17.5
MALE SAE	1/2 in., 3/4-16	BV8PMST	1.47	37.3	1.03	26.2	0.44	11.2	0.63	16.0
MALE ISO	1/4 in.	BV4PMRT	1.34	34.0	0.94	23.9	0.41	10.4	0.75	19.1
MALE ISO	1/2 in.	BV8PMRT	1.47	37.3	1.03	26.2	0.44	11.2	0.92	23.4